


Product Information

DE-F421



Material description:	thermal transfer printable polyester film, white, glossy; UL MH48716*)															
Applications:	automotive and electronics industry															
Label stock thickness:	50 µm ± 10%															
Adhesive:	AS4: Acrylic adhesive, solvent-based, temperature sensitive															
Adhesive thickness:	27 µm ± 10%															
Adhesion:	very strong adhesive															
Adhesion power:	<table><tr><td>stainless steel:</td><td>20,6 N/25 mm</td><td>FTM1</td></tr><tr><td>glass:</td><td>21,9 N/25 mm</td><td>FTM1</td></tr><tr><td>polypropylene:</td><td>17,5 N/25 mm</td><td>FTM1</td></tr><tr><td>automotive paint:</td><td>19,5 N/25 mm</td><td>FTM1</td></tr><tr><td>PBT:</td><td>18,0 N/25 mm</td><td>FTM1</td></tr></table>	stainless steel:	20,6 N/25 mm	FTM1	glass:	21,9 N/25 mm	FTM1	polypropylene:	17,5 N/25 mm	FTM1	automotive paint:	19,5 N/25 mm	FTM1	PBT:	18,0 N/25 mm	FTM1
stainless steel:	20,6 N/25 mm	FTM1														
glass:	21,9 N/25 mm	FTM1														
polypropylene:	17,5 N/25 mm	FTM1														
automotive paint:	19,5 N/25 mm	FTM1														
PBT:	18,0 N/25 mm	FTM1														
Liner:	glassine															
Liner thickness:	56 µm ± 10%															
Temperature range:	- 40 °C to + 150 °C															
Application temperature:	> + 10 °C															
Print method:	thermal transfer															
Ribbon recommendation:	DE-R89*), DE-R25*), DE-R22*), DE-R21*) (in each case on unprinted material surface)															
Shelf life:	1 year at max. 20-25 °C and 40-50 % relative humidity without direct insolation (In case of non-compliance of conditions the consequence could be adhesive adherence which might entail problems in processing the labels)															

*) UL recognised component 

Warranty:

Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.5

create date 2025-01-15